

DWPI

DERWENT-ACC-NO: 1999-364231

DERWENT-WEEK: 199931

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Antenna installation alignment aid for satellite
broadcasting - has

remote control unit enabling installer to select channels on
set-top satellite

tuner while adjusting antenna and viewing picture quality on
outdoor TV monitor

PATENT-ASSIGNEE: YAGI ANTENNA KK[YAGI]

PRIORITY-DATA: 1997JP-0298864 (October 30, 1997)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
--------	----------	----------

PAGES	MAIN-IPC	
-------	----------	--

JP 11136708 A	May 21, 1999	N/A	006
---------------	--------------	-----	-----

H04N 017/00

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
--------	-----------------	---------

APPL-DATE		
-----------	--	--

JP11136708A	N/A	1997JP-0298864
-------------	-----	----------------

October 30, 1997

INT-CL (IPC): G05D003/00; H01Q003/02 ; H04N005/00 ;

H04N005/44 ;

H04N007/20 ; H04N017/00 ; H04N017/04

ABSTRACTED-PUB-NO: JP11136708A

BASIC-ABSTRACT: NOVELTY - The signals from the antenna and from
the installer's

remote control are modulated and fed to the satellite receiver
via an indoor

test unit. The remote control signals are supplied to the
receiver by a

light-emitting unit being placed near it which is connected to
the indoor test

unit. This unit converts the AV output of the receiver to a
channel in the

VHF/VHF band and feeds it back to the outdoor unit where it is
displayed on a

small monitor. The technician then alters the antenna position
until a clear

picture is obtained.

USE - For setting-up an antenna to receive satellite
broadcasting.

ADVANTAGE - Remote control of the tuner operations and local
monitor enable.

installer to optimise antenna position:


DESCRIPTION OF DRAWING(S) - The figure shows the schematic block diagram of the alignment aid used with a satellite TV receiver.

(1) Tuner; (3) Coaxial cable; (4) Indoor unit; (6) Light emission unit; (8) Outdoor unit; (10) Small sized TV monitor; (14) Antenna for satellite broadcast reception.

CHOSEN-DRAWING: Dwg.1/4

DERWENT-CLASS: W02 W03

EPI-CODES: W02-B08A5; W03-A02C5; W03-A16A; W03-A18A9;



ANTENNA DIRECTION ADJUSTING DEVICE

Patent Number: JP11136708
Publication date: 1999-05-21
Inventor(s): SUGIYAMA JUN; HIGUCHI HIROBUMI
Applicant(s): YAGI ANTENNA CO LTD
Requested Patent: JP11136708
Application Number: JP19970298864 19971030
Priority Number(s):
IPC Classification: H04N17/00 ; H01Q3/02 ; H04N5/00 ; H04N5/44 ; H04N7/20 ; H04N17/04
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To adjust a direction of an antenna correctly by confirming a reception state at an antenna installation site and controlling remotely a tuner placed on a remote site.
SOLUTION: An indoor unit 4 and a light emitting unit 6 are placed on the site of a tuner 1, an outdoor unit 8 and a compact television monitor 10 are placed on the installation site of an antenna 14. A remote control signal is sent from the outdoor unit 8 to the indoor unit 4 by the operation of the remote controller 1 and then the light emitting unit 6 generates an infrared ray remote control signal to activate the tuner 1. The indoor unit 4 modulates an antenna level display video and a television video or the like outputted from the tuner 1 into a television signal of a VHF/UHF band to output. The outdoor unit 8 displays the television signal sent from the indoor unit 4 on the compact television monitor 10. An antenna adjustment personnel adjusts the direction of the antenna while observing the antenna level display video or the like displayed on the monitor 10.

Data supplied from the esp@cenet database - 12